



Alloy Machined Side-Eject Tine - .472MT x 7.000L x .880OD R9990076



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.472 in (11.9mm)
C - Tine Length	7 in (178mm)
D - Tine Tip Outside (Hole) Dia.	.880 in (22.4mm)
E - Tine Tip Inside (Core) Dia.	.600 in (15.2mm)
F - Tine Wall Thickness	.140 in (3.5mm)
Savings	Volume Buy

Fits Models

Redexim Verti-Drain

Pekerti Jaya Sdn. Bad

45 Jalan Industri USJ 1/5, Taman Perindustrian USJ 1 Subang Jay, 47600
603-80216684

<https://pekertijaya.rrproducts.com/>