

# Alloy Hollow Tine - .750MT x 5.750L x .470OD

**.4700D** R108-9132





#### **Details**

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

## **Replaces**

Toro 108-9132

## **Specifications**

Manufacturer R&R Products
A - Tine Type Alloy Hollow
B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 5.75 in (146mm) D - Tine Tip Outside .470 in (11.9mm)

(Hole) Dia.

E - Tine Tip Inside .300 in (7.6mm)

(Core) Dia.

F - Tine Wall .058 in (1.5mm)

**Thickness** 

#### **Fits Models**

Toro Fairway Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Pekerti Jaya Sdn. Bad

45 Jalan Industri USJ 1/5, Taman Perindustrian USJ 1 Subang Jay, 47600

https://pekertijaya.rrproducts.com/



R108-9132

# Alloy Hollow Tine - .750MT x 5.750L x .4700D



Toro ProCore 648s

**Pekerti Jaya Sdn. Bad**45 Jalan Industri USJ 1/5, Taman Perindustrian USJ 1 Subang Jay, 47600
603-80216684

https://pekertijaya.rrproducts.com/