

Alloy Machined Side-Eject Tine - .375MT x 3.500L x .565OD



R201631



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Machined Side-

Eject

B - Tine Mounting .375 in (9.5mm)

Dia.

C - Tine Length 3.5 in (89mm)
D - Tine Tip Outside .565 in (14.4mm)

(Hole) Dia.

E - Tine Tip Inside .435 in (11mm)

(Core) Dia.

F - Tine Wall .062 in (1.6mm)

Thickness

Fits Models

Greencare CoreMaster
John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Toro Greens Aerator

Pekerti Jaya Sdn. Bad

45 Jalan Industri USJ 1/5, Taman Perindustrian USJ 1 Subang Jay, 47600 603-80216684