



Alloy Hollow Tine - .750MT x 6.500L x .600OD R201658



Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	6.5 in (165mm)
D - Tine Tip Outside (Hole) Dia.	.600 in (15.2mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.072 in (1.8mm)

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Pekerti Jaya Sdn. Bad

45 Jalan Industri USJ 1/5, Taman Perindustrian USJ 1 Subang Jay, 47600
603-80216684

<https://pekertijaya.rrproducts.com/>