



Alloy Machined Side-Eject Tine with Carbide Tip - .625MT x 6.000L x .525OD

R201710



Details

These alloy tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treatment facility. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject with Carbide Tip
B - Tine Mounting Dia.	.625 in (15.9mm)
C - Tine Length	6 in (152mm)
Carbide Tip	Carbide Tip
D - Tine Tip Outside (Hole) Dia.	.525 in (13.3mm)
E - Tine Tip Inside (Core) Dia.	.350 in (8.9 mm)
F - Tine Wall Thickness	.072 in (1.8mm)

Fits Models

Jacobsen Aero King PT2448
Jacobsen Aero King T1224
Jacobsen Verator VA-24

Pekerti Jaya Sdn. Bad

45 Jalan Industri USJ 1/5, Taman Perindustrian USJ 1 Subang Jay, 47600
603-80216684

<https://pekertijaya.rrproducts.com/>